



中国认可
国际互认
检测
TESTING
CNAS L4065



2016191719D

Report No.:
报告编号: MED20160805U01

检 验 报 告

TEST REPORT

NAME OF SAMPLE: 36V Lithium Ion Battery Pack

产品名称: 36V 鋰電池組

CLIENT: Melton International L.L.C

委托单位: 美爾頓車業(東莞)有限公司

CLASSIFICATION OF TEST: Commission test

检验类别: 委托检测

广州邦禾检测技术有限公司

Guangzhou MCM Certification and Testing Co., Ltd



Applicant information 申請資料	
Name of samples 样品名称	36V Lithium Ion Battery Pack 36V 鋰電池組
Type/ Model 型号规格	BL07 36V 11Ah 396Wh
Trade mark 商标	TranzX
Commission by 委托单位	Melton International L.L.C 美爾頓車業（東莞）有限公司
Commissioner address 委托单位地址	New City Science Ind Liaobu Town Dong Guan City China 廣東省東莞市寮步鎮新城科技工業園
Manufacturer 制造商	Melton International L.L.C 美爾頓車業（東莞）有限公司
Manufacturer address 制造商地址	New City Science Ind Liaobu Town Dong Guan City China 廣東省東莞市寮步鎮新城科技工業園
Factory 生产厂	Melton International L.L.C 美爾頓車業（東莞）有限公司
Factory address 生产厂地址	New City Science Ind Liaobu Town Dong Guan City China 廣東省東莞市寮步鎮新城科技工業園
Appearance 样品外观颜色	Black 黑色
Sample status 样品状态	Good 完好
Package of goods 样品外包装	—
Quantity of sample 样品数量	41pcs
Sample identification 样品标识序号	b1#~b16# ; c1#~c25#
Reference standard 参考标准	MH/T1052-2013 《Tests for lithium batteries transported by air》 MH/T1052-2013 《航空运输锂电池测试规范》
Receiving date 接样日期	2016.08.05
Completing date 完成日期	2016.08.22

Test Conclusion

测试结论

No.序号	Name of test 测试项目名称	Testing standard 测试标准	Test result 测试结果	Conclusion 本 项结论	Remarks 备注
1	Altitude simulation 高度模拟	UN Manual of Tests and Criteria ST/SG/AC.10/11/Rev.5/ amend.2, 38.3. 联合国《关于危险货物运 输的建议书试验和标准 手册》ST/SG/AC. 10/11/ Rev. 5/amend. 2, 38. 3.	See Appendix 1 见附表 1	Passed 合格	/
2	Thermal test 温度试验		See Appendix 2 见附表 2	Passed 合格	/
3	Vibration 振动		See Appendix 3 见附表 3	Passed 合格	/
4	Shock 冲击		See Appendix 4 见附表 4	Passed 合格	/
5	External Short-circuit 外部短路		See Appendix 5 见附表 5	Passed 合格	/
6	Impact 撞击		See Appendix 6 见附表 6	Passed 合格	/
	Crush 挤压		/	/	N/A 不适用
7	Overcharge 过度充电		See Appendix 7 见附表 7	Passed 合格	/
8	Forced discharge 强制放电		See Appendix 8 见附表 8	Passed 合格	/

Conclusion/结论:

The 36V Lithium Ion Battery Packs submitted by Melton International L.L.C had passed the test items of UNITED NATIONS "Recommendations on the Transport of Dangerous Goods, Manual of Test and Criteria ST/SG/AC.10/11/Rev.5/amend.2, 38.3.

由美爾頓車業（東莞）有限公司送检的 36V 鋰電池組符合联合国《关于危险货物运输的建议书 试验和标准手册》ST/SG/AC. 10/11/Rev. 5/amend. 2, 38. 3 的要求。

Seal/检验专用章:
Date of issue:/日期: Aug. 23, 2016

WARM PROMPT: This test report can be used only for areas excluding Shanghai (not including the use of applying for the certification for safe transport of Shanghai Research Institute of Chemical Industry).

温馨提示: 此份报告适用于“非上海地区”(不适用于申请上海化工鉴定书)。

Approver: Liang Hongcheng

Checker: Hu Pingfei

Tester: Huang Yining

批准: *Liang Hongcheng*


审核: *Hu Pingfei*

测试: *Huang Yining*

Photos of samples and markings

样品及标识照片

Battery (BL07 36V 11Ah 396Wh)



附表 2

[illegible]

Appendix 3

附表 3

[illegible]

Appendix 5

附表 5

Test Items 测试项目	External short circuit 外部短路		
1,1	Test procedure 测试步骤		
	The cell or battery to be tested shall be temperature stabilized so that its external case temperature reaches $55\pm 2^{\circ}\text{C}$ and then the cell or battery shall be subjected to a short circuit condition with a total external resistance of less than $0,1\text{ohm}$ at $55\pm 2^{\circ}\text{C}$. This short circuit condition is continued for at least one hour after the cell or battery external case temperature has returned to $55\pm 2^{\circ}\text{C}$, the cell or battery must be observed for a further six hour for the test to be concluded. 保持试验环境温度稳定在 $55\pm 2^{\circ}\text{C}$，以使电芯或电池样品外表温度达到 $55\pm 2^{\circ}\text{C}$，然后，在此温度下，将其正负极用小于 $0,1$ 欧姆的线路短接，待电芯或电池的外表温度恢复到 $55\pm 2^{\circ}\text{C}$ 之后再持续 1 小时以上，对电芯或电池必须进一步观察 6 个小时才能下结论。		
1,2	Sample status 样品状态		
	b1#~b4#, at first cycle in fully charged states. b1#~b4#在第一个循环完全充电的电池。		
	b5#~b8#, after 50 cycles ending in fully charged states. b5#~b8#，在第五十个循环完全充电的电池。		
1,3	Result 测试结果		
Sample No. 样品编号	Max. External Temperature 样品表面最高温度 ($^{\circ}\text{C}$)	Test result 测试结果	Remark 备注
b1#	55,9	O	/
b2#	56,8	O	/
b3#	56,4	O	/
b4#	57,0	O	/
b5#	55,7	O	/
b6#	56,2	O	/
b7#	55,9	O	/
b8#	56,7	O	/
Note: D -Disassembly, R -Rupture, F-Fire, O- no disassembly, no rupture, no fire. 注： D- 解体； R- 破裂； F - 起火； O-无解体、无破裂、无起火。			

Appendix 6

附表 6

Test Items 测试项目	Impact 撞击		
1,1	Test procedure 测试步骤 The sample cell or component cell is to be placed on a flat smooth surface. A 15,8 mm $\pm$ 0,1mm diameter, at least 6 cm long, or the longest dimension of the cell, whichever is greater, Type 316 stainless steel bar is to be placed across the centre of the sample. A 9,1 kg $\pm$ 0,1 kg mass is to be dropped from a height of 61 $\pm$ 2,5 cm at the intersection of the bar and sample in a controlled manner using a near frictionless, vertical sliding track or channel with minimal drag on the falling mass. The vertical track or channel used to guide the falling mass shall be oriented 90 degrees from the horizontal supporting surface. The test sample is to be impacted with its longitudinal axis parallel to the flat surface and perpendicular to the longitudinal axis of the 15,8mm $\pm$ 0,1mm diameter curved surface lying across the centre of the test sample. Each sample is to be subjected to only a single impact. 样品电芯或组成电芯被放置平坦表面上。一根直径为 15,8$\pm$0,1 毫米, 长度至少 6 厘米(或该电芯的最大尺寸, 以较大者为准) 的 316 型不锈钢棒横放在样品的中心。一个重达 9,1 $\pm$ 0,1 千克的铁锤从 61$\pm$2,5 厘米高处以几乎无摩擦和零拉力的姿态沿垂直轨道或通道跌落至不锈钢棒与样品的交结点上。用以引导跌落的垂直轨道或通道应与水平支撑面成 90°。被撞击的圆柱形电池的纵轴应与不锈钢棒平面表面平行, 并与横放在样品中心直径为 15,8 毫米弯曲表面的纵轴垂直。每只样品只经受一次撞击。		
1,2	Sample status 样品状态 C1#~C5#, at first cycle at 50% of the design rated capacity; C1#~C5#, 在第一个循环 50%的额定容量;		
	Result 测试结果		
Sample No. 样品编号	Max. External Temperature 样品表面最高温度 (°C)	Test result 测试结果	Remark 备注
C1#	23,6	O	/
C2#	22,9	O	/
C3#	23,3	O	/
C4#	23,6	O	/
C5#	23,0	O	/

Note: D -Disassembly, F-Fire, O- no disassembly, no fire.
注: D- 解体; F - 起火; O-无解体、无起火。

Appendix 7

附表 7

Test Items 测试项目	Overcharge 过度充电		
1,1	Test procedure 测试步骤		
	When the manufacturer's recommended charge voltage is not more than 18V, the minimum voltage of the test shall be the lesser of two times the maximum charge voltage of the or 22V 如果厂家推荐的充电电压不超过 18V, 本测试的最小充电电压应该是两倍的厂家推荐最大充电电压或者是 22V	/	
	When the manufacturer's recommended charge voltage is more than 18V, the minimum voltage of the test shall be 1,2 times maximum charge voltage 如果厂家推荐的充电电压超过 18V, 本测试的最小充电电压应该为 1, 2 倍的厂家推荐最大充电电压		
	The manufacturer's recommended maximum charge voltage is 42,0V. The manufacturer's recommended maximum continuous charge current is 5,0A. The voltage of the test is 50,4V. And the Current is 10,0A. 厂家推荐最大充电电压为 42, 0V, 厂家推荐最大充电电流为 5, 0A. 测试的电压为 50, 4V, 电流为 10, 0A。		
1,2	Sample status 样品状态		
	b9#~b12#, at first cycle in fully charged states. b9#~b12#, 在第一个循环完全充电的电池。		
	b13#~b16#, after 50 cycles ending in fully charged states. b13#~b16#, 在第五十个循环完全充电的电池。		
1,3	Result 测试结果		
Sample No. 样品编号	Voltage Before test (V) 测试前开路电压 (V)	Test result 测试结果	Remark 备注
b9#	41,7	O	/
b10#	41,7	O	/
b11#	41,8	O	/
b12#	41,7	O	/
b13#	41,7	O	/
b14#	41,7	O	/
b15#	41,7	O	/
b16#	41,8	O	/
Note: D -Disassembly, F-Fire, O- no disassembly, no fire. 注: D- 解体; F - 起火; O-无解体、无起火。			

Appendix 8

附表 8

Test Items 测试项目	Forced discharge 强制放电				
1,1	Test procedure 测试步骤				
	Each cell shall be forced discharged at ambient temperature by connecting it in series with a 12V D. C. power supply at an initial current equal to the maximum discharge current specified the manufacturer The specified discharge current is to be obtained by connecting a resistive load of the appropriate size and rating in series with the test cell, Each cell shall be forced discharged for a time interval (in hours) equal to its rated capacity divided by the initial test current(in ampere). 在 20±5℃的环境温度下,将单个电芯连接在 12V 的直流电源及所串联的适当大小电阻负荷回路上进行强制放电,此直流电源提供每个电芯初始电流为制造厂指定的最大放电电流,放电时间为额定容量除以初始电流。				
1,2	Sample status 样品状态				
	C6#~C15#, at first cycle in fully discharged states; C6#~C15#, 在第一个循环完全放电的电芯;				
	C16#~C25#, after 50 cycles ending in fully discharged states; C16#~C25#, 在第五十个循环完全放电的电芯;				
1,3	Result 测试结果				
Sample No. 样品编号	Voltage Before test 测试前开路电压 (V)	Test result 测试结果	Sample No. 样品编号	Voltage Before test 测试前开路电压 (V)	Test result 测试结果
C6#	3,298	O	C16#	3,268	O
C7#	3,233	O	C17#	3,262	O
C8#	3,236	O	C18#	3,268	O
C9#	3,262	O	C19#	3,266	O
C10#	3,262	O	C20#	3,262	O
C11#	3,263	O	C21#	3,238	O
C12#	3,228	O	C22#	3,233	O
C13#	3,236	O	C23#	3,236	O
C14#	3,262	O	C24#	3,238	O
C15#	3,263	O	C25#	3,268	O

Note: D -Disassembly, F-Fire, O- no disassembly, no fire.

注: D- 解体; F - 起火; O-无解体、无起火。

注 意 事 项

Important

1. 本报告无检验单位检验专用章、骑缝章无效。

The test report is invalid without the special seal for testing and Paging seal of Guangzhou MCM Certification and Testing Co., Ltd.

2. 未经本试验室书面同意，不得部分地复制本报告。

Nobody is allowed to photocopy or partly photocopy this test report without written permission of Guangzhou MCM Certification and Testing Co., Ltd.

3. 本报告无批准人、审核人及检测人签名无效。

The test report is invalid without the signatures of Approver, Checker and Tester.

4. 本报告涂改无效。

The test report is invalid if altered.

5. 对检验报告若有异议，应于收到报告之日起十五天内向检验单位提出。

Objections to the test report must be submitted to Guangzhou MCM Certification and Testing Co., Ltd. Within 15 days.

6. 本报告中以逗号代替小数点。

Throughout this report a comma is used as the decimal separator.

7. 本报告仅对来样负责。

The test report is valid for the tested samples only.

检测单位：广州邦禾检测技术有限公司

Laboratory: Guangzhou MCM Certification and Testing Co., Ltd

地 址：中国 广州市番禺区市广路钟三路段 13 号之一

Address: 1 F No.13, Zhong San Section, ShiGuang Road, Panyu District, Guangzhou City, Guangdong Province, China.

电 话：0086-20-34777662

0086-20-34777663

传 真：0086-20-34777665-609

Email: mark.miao@mcmtek.com

Web: [Http://www.mcmtek.com](http://www.mcmtek.com)